



NOTCH DECKING AS REQUIRED AT RAIL POST LOCATIONS

3X6, 3X8 AND 3X10 DECKING LAID OUT IN RANDOM PATTERN

NOTES:

1. UNLESS OTHERWISE SPECIFIED, DECKING MATERIAL SHALL BE ROUGH SAWN D.F. #2 OR BETTER, PT ACQ/CBA, OR APPROVED EQUAL.
2. DECKING TO BE SECURED TO BEAMS AND JOISTS WITH 5/16" x 6" GRK® RSS FASTNER, OR APPROVED EQUAL.

ALUMINUM NON-SLIP TRENDS, BROWN IN COLOR, INSTALLED ON THE CENTERLINE OF EVERY THIRD DECK BOARD
 -USE HANDI-TRENDS OR APPROVED EQUAL
 -INSTALL PER MANUFACTURER'S SPECIFICATIONS
 -FIELD ADJUST SPACING AS REQUIRED

DECK FASTENER
 -SEE NOTE 2



City of Bellevue

TITLE:

TRAIL - FOOTBRIDGE/BOARDWALK - WITH PIN PILE FOOTINGS - SAFETY RAIL OPTION - DECKING PLAN

DRAWING #:	PK-TR-09G
SCALE:	N.T.S.
REVISION DATE:	03-2021
DEPARTMENT:	PARKS